



WATERTIGHT JUNCTION BOXES

SMOOTH SIDES

IP 65

TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU	
Standards Amends	EN 60670-1:2005+A1:2013 Boxes , Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements EN 60529 Degrees of Protection , Enclosures, IP Rate	
Halogen Free	Technopolymer material Halogen free - EN 60754-2 :2014+A1: 2020	
Applications	Indoor – Outdoor - Residential – Industrial Plastic box with Hinged Screwed Lid General Proposes – Industrial etc	
Installations	Exposed – Wall mounted	
	Wiring, Power, Lighting, Automation, Telecom, CCTV, RES	
		
Material	Modified Technical Polymer	
Characteristics	IP Rate	65
	Glow Wire Test	650 °C
	Resistance - UV	R
	Resistance - Chemicals	R
	Resistance - impact	R
	Dielectric Strength	-25 °C +60 °C
	Color	Grey RAL7035



HF Halogen FREE



IP65



TYPE	190x145	245x190	300x215	380x300
CODE	32-21030-190	32-21031-245	32-21032-300	32-21033-380
A _mm	145	190	215	300
B _mm	190	245	300	380
C _mm	70	90	125	125
PACKING / pcs	24	16	6	4

